

SAFETY DATA SHEET

1. Identification

Product number 1000007157
Product identifier **18 OZ ADASEAL STRIP-EASE LB 12PK**
Revision date 03-18-2015
Company information ADASEAL INTERNATIONAL INC.
5468 HWY 70 W.
WAVERLY, TN 37185 United States
Company phone General Assistance 931-296-2291
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 02
Supersedes date 08-05-2014
Recommended use Remover
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Germ cell mutagenicity Category 1
Carcinogenicity Category 1
Reproductive toxicity Category 2
Specific target organ toxicity, single exposure Category 1
Specific target organ toxicity, repeated exposure Category 2
Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label).
Storage Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methylene Chloride		75-09-2	60 - 80
Butane		106-97-8	2.5 - 10
Methanol		67-56-1	2.5 - 10
Propane		74-98-6	2.5 - 10
Toluene		108-88-3	2.5 - 10
Propylene Oxide		75-56-9	0.1 - 1
Other components below reportable levels			1 - 2.5

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or Poison Control Center immediately. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms persist.
Skin contact	Call a physician or Poison Control Center immediately. Get medical attention if irritation develops or persists.
Eye contact	Get medical attention if irritation develops or persists. Call a physician or Poison Control Center immediately.
Ingestion	Have victim rinse mouth thoroughly with water. Get medical attention immediately. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
Most important symptoms/effects, acute and delayed	Dizziness. Nausea. Irritation of eyes and mucous membranes. Skin irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	In case of shortness of breath, give oxygen. Immediate medical attention is required. If exposed or concerned: get medical attention/advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media	Not available.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Cool containers with flooding quantities of water until well after fire is out. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Use personal protective equipment. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Clean contaminated surface thoroughly. Wipe up with absorbent material (e.g. cloth, fleece). For waste disposal, see section 13 of the SDS. This material and its container must be disposed of as hazardous waste.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Use only with adequate ventilation. Do not breathe gas. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Keep locked-up. Keep away from heat, sparks, and flame. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. The pressure in sealed containers can increase under the influence of heat. Keep at temperature not exceeding 49°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep in a well-ventilated place. This material can accumulate static charge which may cause spark and become an ignition source. Keep this material away from food, drink and animal feed. Refrigeration recommended. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol (NFPA 30B)

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Methanol (CAS 67-56-1)	PEL	260 mg/m3
		200 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m3
		250 ppm
		260 mg/m3
Propane (CAS 74-98-6)	TWA	200 ppm
		1800 mg/m3
		1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
		375 mg/m3
	TWA	100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Methylene Chloride (CAS 75-09-2)	0.3 mg/l	Dichloromethane	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

Methanol (CAS 67-56-1) Can be absorbed through the skin.
Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Methanol (CAS 67-56-1) Skin designation applies.
Toluene (CAS 108-88-3) Skin designation applies.

US - Tennessee OELs: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Avoid exposure - obtain special instructions before use.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear chemical goggles.
Hand protection	Wear appropriate chemical resistant gloves.
Skin protection	
Other	Wear appropriate chemical resistant gloves. Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended.
Skin protection	
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. When using do not eat or drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Aerosol.

Color Opaque.

Odor Not available.

Odor threshold Not available.

pH Not applicable estimated

Melting point/freezing point Not available.

Initial boiling point and boiling range 103.55 °F (39.75 °C) estimated

Flash point -156.0 °F (-104.4 °C) estimated estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.9 % estimated

Flammability limit - upper (%) 9.5 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 30 - 40 psig @ 70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Specific gravity 1.038 estimated estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition. Stable at normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates. Fluorine. Caustics. Chlorine.

Hazardous decomposition products May include oxides of oxides of carbon. May include oxides of phosphorus.

11. Toxicological information**Information on likely routes of exposure**

Ingestion Expected to be a low ingestion hazard.

Inhalation May cause damage to organs by inhalation. May cause damage to organs through prolonged or repeated exposure by inhalation. Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Dizziness. Nausea. Irritation of eyes and mucous membranes. Skin irritation.

Information on toxicological effects

Acute toxicity Acute LC50: 249 mg/l/4h, Rat, Inhalation

Product	Species	Test Results
18 OZ ADASEAL STRIP-EASE LB 12PK (CAS Mixture)		
Acute		
<i>Inhalation</i>		
LC50	Rat	249 mg/l/4h
<i>Oral</i>		
LD50	Rat	
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Methanol (CAS 67-56-1)		
Acute		
<i>Inhalation</i>		
LC50	Cat	85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours
	Mouse	79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours 82.1 mg/l, 6 Hours
<i>Oral</i>		
LD50	Monkey	6000 mg/kg
	Rat	1187 - 2769 mg/kg

Components	Species	Test Results
<i>Other</i> LD50	Mouse	6000 mg/kg
Methylene Chloride (CAS 75-09-2)		
Acute <i>Dermal</i> LD50	Rat	> 2000 mg/kg, Days
<i>Inhalation</i> LC50	Mouse	49 mg/l, 7 Hours
Propane (CAS 74-98-6)		
Acute <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h
Propylene Oxide (CAS 75-56-9)		
Acute <i>Dermal</i> LD50	Rabbit	950 - 1250 mg/kg, 4 Hours 1.5 ml/kg, 4 Hours
<i>Inhalation</i> LC50	-	4197 ppm, 4 Hours 4124 mg/m3, 4 Hours
<i>Oral</i> LD50	Rat	382 - 587 mg/kg
Toluene (CAS 108-88-3)		
Acute <i>Dermal</i> LD50	Rabbit	> 5000 mg/kg, 24 Hours
<i>Inhalation</i> LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 12.5 - 28.8 mg/l, 4 Hours
<i>Oral</i> LD50	Rat	5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Not expected to be hazardous by OSHA criteria.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Germ cell mutagenicity Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria. May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methylene Chloride (CAS 75-09-2)	2B Possibly carcinogenic to humans.
Propylene Oxide (CAS 75-56-9)	2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Methylene Chloride (CAS 75-09-2)

Reasonably Anticipated to be a Human Carcinogen.

Propylene Oxide (CAS 75-56-9)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity	Suspected of damaging fertility or the unborn child. Not expected to be hazardous by OSHA criteria. Not expected to be hazardous by WHMIS criteria.
Specific target organ toxicity - single exposure	Causes damage to organs. Skin. Respiratory system. Central nervous system. Eyes. Gastrointestinal tract.
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Danger of serious damage to health by prolonged exposure. Not expected to be hazardous by WHMIS criteria. May cause damage to organs through prolonged or repeated exposure.
Further information	Danger of very serious irreversible effects.

12. Ecological information

Ecotoxicity	LC50: 184 mg/L, Fish, 96.00 Hours EC50: 289 mg/L, Daphnia, 48.00 Hours Harmful to aquatic life with long lasting effects.
--------------------	---

Product	Species		Test Results
18 OZ ADASEAL STRIP-EASE LB 12PK (CAS Mixture)			
Aquatic			
Crustacea	EC50	Daphnia	289 mg/L, 48 Hours
Fish	LC50	Fish	184 mg/L, 96 Hours
Components			
Methanol (CAS 67-56-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Methylene Chloride (CAS 75-09-2)			
Aquatic			
Algae	IC50	Algae	500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1689.5 mg/L, 48 Hours
		Water flea (Daphnia magna)	1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	140.8 - 277.8 mg/l, 96 hours
Propylene Oxide (CAS 75-56-9)			
Aquatic			
Crustacea	EC50	Daphnia	350 mg/L, 48 Hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Butane 2.89

Partition coefficient n-octanol / water (log Kow)	
Methanol	-0.77
Methylene Chloride	1.25
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Dispose of this material and its container at hazardous or special waste collection point. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Methanol (CAS 67-56-1)	U154
Methylene Chloride (CAS 75-09-2)	U080
Toluene (CAS 108-88-3)	U220

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information



DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1(PGIII)
Label(s)	2.1, 6.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Transport hazard class(es)	
Class	2.1
Subsidiary risk	6.1(PGIII)
Label(s)	2.1, 6.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10P
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information**Passenger and cargo aircraft** Allowed.**Cargo aircraft only** Allowed.**Packaging Exceptions** LTD QTY**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS**Transport hazard class(es)****Class** 2.1**Subsidiary risk** 6.1(PGIII)**Label(s)** 2.1+6.1**Packing group** Not applicable.**Environmental hazards****Marine pollutant** No.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.**Packaging Exceptions** NOT a LTD QTY**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.**DOT****IATA; IMDG****15. Regulatory information****US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methanol (CAS 67-56-1) Listed.

Methylene Chloride (CAS 75-09-2) Listed.

Propylene Oxide (CAS 75-56-9) Listed.

Toluene (CAS 108-88-3) Listed.

SARA 304 Emergency release notification

Propylene Oxide (CAS 75-56-9) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2) Cancer

Heart
Central nervous system
Liver
Skin irritation
Eye irritation

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
---------------	------------	---------------------	-----------------------------	--	--

Propylene Oxide	75-56-9	100	10000 lbs		
-----------------	---------	-----	-----------	--	--

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Methylene Chloride	75-09-2	60 - 80
Methanol	67-56-1	2.5 - 10
Toluene	108-88-3	2.5 - 10
Propylene Oxide	75-56-9	0.1 - 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

Butane (CAS 106-97-8)
Methanol (CAS 67-56-1)
Methylene Chloride (CAS 75-09-2)
Propane (CAS 74-98-6)
Propylene Oxide (CAS 75-56-9)
Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Methylene Chloride (CAS 75-09-2) Listed: April 1, 1988
Propylene Oxide (CAS 75-56-9) Listed: October 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) Listed: March 16, 2012
Toluene (CAS 108-88-3) Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3) Listed: August 7, 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-05-2014

Revision date 03-18-2015

Version # 02

Disclaimer We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Product Uses
Physical & Chemical Properties: Multiple Properties
GHS: Classification