

# SAFETY DATA SHEET

## Brake Lube 411 Aerosol

### 1. Product And Company Identification

**GHS product identifier:** Brake Lube 411 Aerosol  
**Other means of identification:** Not available.

**Relevant identified uses of the substance or mixture and uses advised against:**  
Silicone Lubricant

**Supplier's details:** Adaseal International Inc.  
5468 Hwy 70 W  
Waverly, TN. 37185  
Phone: 931-296-2291  
Toll Free: 800-521-2521  
Fax: 931-296-5239  
E-Mail: adaseal2@adaseal.com

**Emergency telephone number:** CHEMTREC, **24 hours/day, 7 days/week**  
U.S.: 1-800-424-9300  
International: +1-703-527-3887

**SDS Date of Preparation:** 06/28/2018

### 2. Hazards Identification

**GHS Classification:**

<b>Physical:</b>	<b>Health:</b>
Gases Under Pressure: Compressed Gas	Non-Hazardous

**GHS Label Elements:**



**Warning!**

Statements of Hazard	Precautionary phrases
Contains gas under pressure; may explode if heated.	Protect from sunlight. Store in a well-ventilated place.

### 3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-Difluoroethane	75-37-6	<1%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First Aid Measures

**Inhalation:** If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

**Skin Contact:** Wash exposed skin with soap and water for several minutes. If skin irritation develops, seek medical

# SAFETY DATA SHEET

## Brake Lube 411 Aerosol

attention.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

**Ingestion:** Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

**Most Important Symptoms:** May cause mild eye or respiratory irritation.

**Indication of Immediate Medical Attention/Special Treatment:** None known.

### 5. Firefighting Measures

**Suitable (and Unsuitable) Extinguishing Media:** Use dry chemical, foam, carbon dioxide, or water spray.

**Specific Hazards Arising from the Chemical:** Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce carbon oxides, formaldehyde, and silicon dioxide. Exposure of containers to heat and flames can cause them to rupture often with violent force.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

### 6: Accidental Release Measures

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Ventilate the area. Wear appropriate protective clothing and equipment.

**Methods and Materials for Containment and Clean-Up:** Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

**Environmental Precautions:** Report release as required by local and national regulations.

### 7. Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes and skin. Avoid breathing gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

**U.F.C. (NFPA 30B) Level 1 Aerosol.**

### 8. Exposure Controls / Personal Protection

**Exposure Guidelines:**

CHEMICAL	EXPOSURE LIMIT
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs

**Appropriate Engineering Controls:** General ventilation should be adequate for normal use. For operations

# SAFETY DATA SHEET

## Brake Lube 411 Aerosol

where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

### Personal Protective Equipment

**Respiratory Protection:** None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

**Gloves:** Impervious gloves recommended to avoid skin contact.

**Eye Protection:** Safety glasses are recommended if eye contact is possible.

**Other Protective Equipment/Clothing:** None required.

## 9. Physical and Chemical Properties

**Appearance and Odor:** Translucent white paste with no odor.

<b>Physical State:</b> Thick liquid under pressure	<b>Odor Threshold:</b> Not determined
<b>pH:</b> Not determined	<b>Specific Gravity:</b> 1.03 (Liquid component)
<b>Initial Boiling Point/Range:</b> Not determined	<b>Vapor Pressure:</b> Not determined
<b>Melting/Freezing Point:</b> Not determined	<b>Vapor Density:</b> (Air = 1) Not determined
<b>Solubility In Water:</b> Not determined	<b>Percent Volatile:</b> Not determined
<b>Viscosity:</b> Not determined	<b>Evaporation Rate:</b> (n-butyl acetate = 1.0): Not determined
<b>Decomposition Temperature:</b> Not available	<b>VOC Content:</b> 11 g/L (Liquid component)
<b>Coefficient Of Water/Oil Distribution:</b> Not determined	<b>Autoignition Temp:</b> Not determined
<b>Flash Point:</b> > 101.1 °C (> 214 °F) CC (Liquid component)	<b>Flame extension:</b> Not determined
<b>Flammability Limits:</b> LEL: 3.7% (1,1-Difluoroethane) UEL: 18% (1,1-Difluoroethane)	<b>Flammability (solid, gas):</b> Not applicable

## 10. Stability and Reactivity

**Reactivity:** Not normally reactive

**Chemical Stability:** Stable under normal storage and handling conditions

**Possibility of Hazardous Reactions:** None expected.

**Conditions to Avoid:** Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

**Incompatible Materials:** Strong oxidizing agents, strong bases, and strong acids.

**Hazardous Decomposition Products:** May produce carbon oxides, formaldehyde, and silicon dioxide.

## 11. Toxicological Information

### Potential Health Effects:

#### Acute Hazards:

**Inhalation:** Vapors can irritate the throat and respiratory tract.

**Skin Contact:** May cause mild irritation.

**Eye Contact:** May cause mild irritation.

# SAFETY DATA SHEET

## Brake Lube 411 Aerosol

**Ingestion:** Swallowing may cause gastrointestinal disturbances.

**Chronic Effects:** None expected

**Carcinogenicity Listing:** None of the components listed is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

### Numerical Measures of Toxicity:

1,1-Difluoroethane: LC50 Inhalation Rat: 437,500ppm/4h

## 12. Ecological Information

### **Ecotoxicity:**

1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated)

**Persistence and Degradability:** No data available for product.

**Bio accumulative Potential:** No data available for product.

**Mobility in Soil:** No data available for product.

**Other Adverse Effects:** No data available

## 13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

## 14. Transport Information

**DOT Hazardous Materials Description:** UN1950, Aerosols, 2.2 LTD QTY

**IMDG Dangerous Goods Description:** UN1950, Aerosols 2.2 LTD QTY

## 15. Regulatory Information

### United States:

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA Hazard Category (311/312):** Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

**California Proposition 65:** Warning not required.

**SAFETY DATA SHEET**  
Brake Lube 411 Aerosol

<b>16. Other Information</b>
------------------------------

REVISION DATE: 06/28/2018

REVISION SUMMARY: New SDS

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

**Notice to reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist