

SAFETY DATA SHEET

Oxime Low Volatility Aluminum Aerosol

1. Product And Company Identification

GHS product identifier: Oxime Low Volatility Aluminum Aerosol
Other means of identification: Not available.

Relevant identified uses of the substance or mixture and uses advised against:
 Silicone sealant

Supplier's details: Adaseal International Inc.
 5468 Hwy 70 W
 Waverly, TN. 37185
 Phone: 931-296-2291
 Toll Free: 800-521-2521
 Fax: 931-296-5239
 E-Mail: adaseal2@adaseal.com

Emergency telephone number: CHEMTREC, **24 hours/day, 7 days/week**
 U.S.: 1-800-424-9300
 International: +1-703-527-3887

SDS Date of Preparation: 07/10/2018

2. Hazards Identification

GHS Classification:

Physical: Gases Under Pressure: Compressed Gas	Health: Skin Sensitization Category 1 Specific Target Organ Toxicity – Repeat Exposure Category 2 (oral)
--	--

GHS Label Elements:



Warning!

Statements of Hazard	Precautionary phrases
Contains gas under pressure; may explode if heated. May cause an allergic skin reaction May cause damage to blood through prolonged or repeated ingestion. Precautionary phrases Response IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. Get medical attention if you feel unwell.	Prevention Do not breathe vapors. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. Wear protective gloves protection. Storage Protect from sunlight. Store in a well-ventilated place. Disposal Dispose of contents and container in accordance with local and national regulations.

SAFETY DATA SHEET

Oxime Low Volatility Aluminum Aerosol

3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-Difluoroethane	75-37-6	<1%
2-Butanone, O,O',O"- (methylsilylidyne) trioxime	22984-54-9	<5%
2-Butanone, O,O', O"- (ethenylsilylidyne) trioxime	2224-33-1	<1%
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane	1760-24-3	<1%
Methyltri (ethylmethylketoxime) silane isomers and oligomers	Not available	<1%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

Skin Contact: Wash exposed skin with soap and water for several minutes. If skin irritation or rash develops, seek medical attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Most Important Symptoms: May cause an allergic skin reaction in some individuals. Vapors may cause mild respiratory irritation. Repeated or prolonged ingestion may cause damage to the blood, cardiovascular, and hematological system.

Indication of Immediate Medical Attention/Special Treatment: None known.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use extinguishing media suitable for surrounding fire.

Specific Hazards Arising from the Chemical: Not classified as flammable but contains a flammable propellant. Contents under pressure. Burning may produce very toxic, flammable formaldehyde; silicon oxides; carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Ventilate the area. Wear appropriate protective clothing and equipment.

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Environmental Precautions: Report release as required by local and national regulations.

SAFETY DATA SHEET

Oxime Low Volatility Aluminum Aerosol

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Conditions for Safe Storage, Including any Incompatibilities: Will evolve methyl ethyl ketoxime (MEKO) when exposed to water or humid air. Store in a cool, dry, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. **U.F.C. (NFPA 30B) Level 1 Aerosol.**

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs
2-Butanone, O,O', O"- (ethenylsilylidyne) trioxime	None established
2-Butanone, O,O',O"- (methylsilylidyne) trioxime	None established
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane	None established
Methyltri (ethylmethylketoxime) silane isomers and oligomers	None established

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

Gloves: Wear impervious gloves to avoid skin contact.

Eye Protection: Safety glasses are recommended if eye contact is possible.

Other Protective Equipment/Clothing: Wear personal protection as needed to avoid skin contact.

9. Physical and Chemical Properties

Appearance and Odor: Gray viscous paste with slight odor.

Physical State: Thick liquid under pressure	Odor Threshold: Not determined
pH: Not determined	Specific Gravity: 1.04 (Liquid component)
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: (Air = 1) Not determined
Solubility In Water: Not determined	Percent Volatile: Not determined
Viscosity: Not determined	Evaporation Rate: (n-butyl acetate = 1.0): Not determined
Decomposition Temperature: Not available	VOC Content: Not determined
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined
Flash Point: Not applicable	Flame extension: Not determined

SAFETY DATA SHEET

Oxime Low Volatility Aluminum Aerosol

Flammability Limits: LEL: 3.7% (1,1-Difluoroethane)
UEL: 18% (1,1-Difluoroethane)

Flammability (solid, gas): Not applicable

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: Forms toxic chemicals on contact with strong oxidizing agents, strong bases, and strong acids. Will evolve methyl ethyl ketoxime (MEKO) when exposed to water or humid air.

Conditions to Avoid: Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

Incompatible Materials: Strong oxidizing agents, strong bases, and strong acids.

Hazardous Decomposition Products: Burning may produce formaldehyde; silicon oxides; carbon oxides.

11. Toxicological Information

Potential Health Effects:

Acute Hazards:

Inhalation: Vapors can irritate the throat and respiratory tract.

Skin Contact: Contains 2-Butanone, O,O', O''- (ethenylsilylidyne) trioxime and 2-Butanone, O,O',O''- (methylsilylidyne) trioxime which may cause an allergic skin reaction.

Eye Contact: May cause mild irritation.

Ingestion: Swallowing may cause gastrointestinal disturbances.

Chronic Effects: Contains 2-Butanone, O,O', O''- (ethenylsilylidyne) trioxime, 2-Butanone, O,O',O''- (methylsilylidyne) trioxime, and distillates (petroleum), straight-run middle which may cause damage to the blood, cardiovascular, and hematological system through prolonged or repeated exposure.

Carcinogenicity Listing: None of the components listed is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

Numerical Measures of Toxicity:

Product ATE:

LD50 Oral > 2,000 mg/kg
LD50 Dermal > 2,000 mg/kg
LC50 Inhalation >5 mg/L

1,1-Difluoroethane:

LC50 Inhalation Rat: 437,500ppm/4h

2-Butanone, O,O',O''- (methylsilylidyne) trioxime:

LD50 Oral Rat 2,643 mg/kg
LD50 Dermal Rat > 2,000 mg/kg

2-Butanone, O,O', O''- (ethenylsilylidyne) trioxime:

LD50 Oral Rat > 2,000 mg/kg
LD50 Dermal Rat > 2,009 mg/kg

N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane:

LD50 Oral Rat 1,897 mg/kg
LD50 Dermal Rabbit > 2,000 mg/kg
LC50 Inhalation Rat: >1.49 - < 2.44 mg/L/4 hr.

Methyltri (ethylmethylketoxime) silane isomers and oligomers: Not determined

SAFETY DATA SHEET

Oxime Low Volatility Aluminum Aerosol

12. Ecological Information

Ecotoxicity:

1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated)
2-Butanone, O,O',O"- (methylsilylidyne) trioxime:
LC50 Oncorhynchus mykiss (rainbow trout) > 120 mg/L/ 96hr
LC50 Daphnia magna (water flea) >120 mg/L/ 48hr
N-beta-(aminoethyl)-gamma aminopropyltrimethoxysilane:
LC50 Brachydanio rerio (zebrafish) 597 mg/L/ 96hr
LC50 Daphnia magna (water flea) 81 mg/L/ 48hr

Persistence and Degradability: No data available for product.

Bio accumulative Potential: No data available for product.

Mobility in Soil: No data available for product.

Other Adverse Effects: No data available

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

DOT Hazardous Materials Description: UN1950, Aerosols, 2.2 LTD QTY

IMDG Dangerous Goods Description: UN1950, Aerosols 2.2 LTD QTY

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ, however, oil spills must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372): None

California Proposition 65:

WARNING: This product can expose you to chemicals including Cobalt titanite green spinel, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm.

SAFETY DATA SHEET
Oxime Low Volatility Aluminum Aerosol

16. Other Information

REVISION DATE: 07/10/2018

REVISION SUMMARY: New SDS

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.