

SAFETY DATA SHEET

Slipkote™ 2000 Anti-Seize Aerosol

1. Product And Company Identification

GHS product identifier: Slipkote™ 2000 Anti-Seize Aerosol
Other means of identification: Not available.

Relevant identified uses of the substance or mixture and uses advised against:
Anti-seize

Supplier's details: Adaseal International Inc.
5468 Hwy 70 W
Waverly, TN. 37185
Phone: 931-296-2291
Toll Free: 800-521-2521
Fax: 931-296-5239
E-Mail: adaseal2@adaseal.com

Emergency telephone number: CHEMTREC, **24 hours/day, 7 days/week**
U.S.: 1-800-424-9300
International: +1-703-527-3887

SDS Date of Preparation: 05/12/2021

2. Hazards Identification

GHS Classification:

Physical:	Health:
Flammable Aerosol Category 1 Gases Under Pressure: Compressed Gas	Non-Hazardous

GHS Label Elements:



Danger!

Statements of Hazard	Precautionary phrases
Contains gas under pressure; may explode if heated. Extremely flammable aerosol.	Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized Container. Do not pierce or burn, even after use. Protect from sunlight. Store in a well-ventilated place.

3. Composition/Information on Ingredients

Component	CAS No.	Amount
1,1-Difluoroethane	75-37-6	1-5%
Copper	7440-50-8	1-5%
Aluminum Powder	7429-90-5	1-5%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade

SAFETY DATA SHEET

Slipkote™ 2000 Anti-Seize Aerosol

secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problem or irritation persists.

Skin Contact: Wash exposed skin with soap and water for several minutes. If skin irritation develops, seek medical attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice or attention.

Ingestion: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Most Important Symptoms: May cause mild irritation to eye and skin.

Indication of Immediate Medical Attention/Special Treatment: None known.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use dry chemical, foam, carbon dioxide, or water spray.

Specific Hazards Arising from the Chemical: Extremely flammable aerosol. Contents under pressure. Burning may produce halogenated compounds, metal oxides and carbon oxides. Exposure of containers to heat and flames can cause them to rupture often with violent force.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Eliminate all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing and equipment.

Methods and Materials for Containment and Clean-Up: Place leaking can in a pail in a well-ventilated area until pressure has dissipated. Collect residual liquid using inert absorbents and place into a suitable container for disposal.

Environmental Precautions: Prevent release to the environment. Report release as required by local and national regulations.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Avoid breathing vapors or gas. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Contents under pressure, do not puncture or incinerate containers.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, well-ventilated area, away from strong oxidizers and other incompatible materials. Do not store in direct sunlight or above 120°F.

U.F.C. (NFPA 30B) Level 1 Aerosol.

SAFETY DATA SHEET

Slipkote™ 2000 Anti-Seize Aerosol

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
1,1-Difluoroethane	1000 ppm TWA AIHA WEELs
Copper (as copper dust)	1 mg/m ³ TWA ACGIH TLV 1 mg/m ³ TWA OSHA PEL
Copper (as copper fume)	0.2 mg/m ³ TWA ACGIH TLV 0.1 mg/m ³ TWA OSHA PEL
Aluminum Powder (as aluminum Al)	1 mg/m ³ TWA ACGIH TLV (respirable) 5 mg/m ³ TWA OSHA PEL (respirable) 15 mg/m ³ TWA OSHA PEL (total dust)

Appropriate Engineering Controls: General ventilation should be adequate for normal use. For operations where the exposure limits may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits.

Personal Protective Equipment

Respiratory Protection: None under normal use conditions. For operations where the exposure limits may be exceeded, a NIOSH approved supplied air respirators recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

Gloves: Impervious gloves recommended to avoid skin contact.

Eye Protection: Safety glasses are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required.

9. Physical and Chemical Properties

Appearance and Odor: Dark metallic copper colored viscous paste with mild odor.

Physical State: Thick liquid under pressure	Odor Threshold: Not determined
pH: Not determined	Specific Gravity: 1.04 (Liquid component)
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: (Air = 1) Not determined
Solubility In Water: Insoluble	Percent Volatile: Not determined
Viscosity: Not determined	Evaporation Rate: (n-butyl acetate = 1.0): Not determined
Decomposition Temperature: Not available	VOC Content: Not determined
Coefficient Of Water/Oil Distribution: Not determined	Autoignition Temp: Not determined
Flash Point: 232 °C (450 °F) COC (Liquid component)	Flame extension: Not determined
Flammability Limits: LEL: 3.7% (1,1-Difluoroethane) UEL: 18% (1,1-Difluoroethane)	Flammability (solid, gas): Extremely flammable aerosol.

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable under normal storage and handling conditions

Possibility of Hazardous Reactions: None expected.

SAFETY DATA SHEET

Slipkote™ 2000 Anti-Seize Aerosol

Conditions to Avoid: Keep away from excessive heat, and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

Incompatible Materials: Strong oxidizing agents, strong bases, and strong acids.

Hazardous Decomposition Products: Burning may produce silicon oxides; carbon oxides.

11. Toxicological Information

Potential Health Effects:

Acute Hazards:

Inhalation: May cause mild irritation.

Skin Contact: May cause mild irritation.

Eye Contact: May cause mild irritation.

Ingestion: Swallowing may cause gastrointestinal disturbances.

Chronic Effects: None expected

Carcinogenicity Listing: None of the components listed is a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA

Numerical Measures of Toxicity:

Product ATE: LD50 Oral >5000 mg/kg

1,1-Difluoroethane: LC50 Inhalation Rat: 437,500ppm/4h

Copper: LD50 Oral Rat: 300-500 mg/kg

Aluminum Powder: LD50 Oral Rat: >5000 mg/kg; LC50 Inhalation Rat: >0.888 mg/l/4h

12. Ecological Information

Ecotoxicity: Very toxic to aquatic life with long lasting effects.

1,1-Difluoroethane: LC50 Fish 719.61 mg/L/ 96hr (Calculated)

Copper: LC50 Daphnia magna 31.8 ug/l/ 48 hr.

Aluminum Powder: Not classified as harmful to the aquatic environment.

Persistence and Degradability: No data available for product.

Bio accumulative Potential: No data available for product.

Mobility in Soil: No data available for product.

Other Adverse Effects: No data available

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

SAFETY DATA SHEET

Slipkote™ 2000 Anti-Seize Aerosol

14. Transport Information

DOT Hazardous Materials Description: UN1950, Aerosols, 2.1 LTD QTY

IMDG Dangerous Goods Description: UN1950, Aerosols 2.1 LTD QTY

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103 This product has a Reportable Quantity (RQ) of 100,000 lbs. based on the RQ for Copper of 5,000 lbs. present at 5% maximum. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Classified under OSHA Hazcom 2012 GHS as per Section 2 of this SDS.

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372):

Aluminum Powder	CAS# 7429-90-5	at 1-5%
Copper	CAS# 7440-50-8	at 1-5%

California Proposition 65: Warning not required.

16. Other Information

REVISION DATE: 05/12/2021

REVISION SUMMARY: New SDS

DATE OF PREVIOUS REVISION: N/A

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist